



SILENT CHAIN WITH ROCKER-PIN

PITCH (in)	CHAIN No.	WIDTH (in)	AVERAGE ULTIMATE TENSILE STRENGTH (lbs)	RIVET PIN LENGTH L (in)	HEIGHT ABOVE PITCH LINE h (in, min.)	HEIGHT H (in, max.)	CHAIN WEIGHT (lbs/ft)
3/8 inch	SC302 (*1)	1/2	1875	0.8	0.2	0.4	0.4
	SC303	3/4	2810	0.9			0.6
	SC304	1	3750	1.1			0.8
	SC305	1 1/4	4690	1.4			0.9
	SC306	1	5620	1.7			1.3
	SC308	2	7500	2.2			1.5
1/2 inch	SC403	3/4	5600	0.9	0.3	0.5	0.8
	SC404	1	7500	1.1			1.0
	SC405	1 1/4	9300	1.4			1.3
	SC406	1 1/2	11200	1.7			1.5
	SC408	2	15000	2.2			2.0
	SC410	2 1/2	18700	2.7			2.5
	SC412	3	22500	3.2			3.0
	SC414	3 1/2	26200	3.7			3.5
3/4 inch	SC606	1 1/2	16900	1.7	0.4	0.8	2.3
	SC608	2	22500	2.2			3.0
	SC610	2 1/2	28100	2.7			3.8
	SC612	3	33800	3.2			4.5
	SC616	4	45000	4.2			6.0
	SC620	5	56200	5.2			7.5
1 inch	SC812	3	45000	3.2	0.5	1.1	6.0
	SC816	4	60000	4.2			8.0
	SC820	5	75000	5.2			10.0
	SC824	6	90000	6.2			12.0

Note : 1). Outside guide chain , distance between guides is 0.460

2). Widths other than listed are available upon request.